

Product Information Sheet

Supplier's name or trade mark: Arlec Electrical Company Limited

Supplier's address : - Unit 18, Cromwell Business Park, Howard way, Newport Pagnell,
MK16 9QS United Kingdom

Model identifier: SL0705GB

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	-		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h)	4	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	350 in a narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3000
On-mode power (P_{on}), expressed in W	4	Standby power (P_{sb}), expressed in W and rounded to the second decimal	-
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without	Height	1	Spectral power distribution in the See image in last page
	Width	1	
	Depth	1	

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,4396 0,4066
Parameters for directional light sources:			
Peak luminous intensity (cd)	290	Beam angle in degrees, or the range of beam angles that can be set	76
Parameters for LED and OLED light sources:			
R9 colour rendering index value	13	Survival factor	
the lumen maintenance factor			
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	-	Colour consistency in McAdam ellipses	2,1
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-

(Example for Spectral diagram)

